



SMC1602A LCM SPECIFICATION


1. MAIN TECHNOLOGY PARAMETER:

Number of Dots:	16 CharacterX2LINE
Operating Voltage:	4.8~5.2V
Operating Current of LCD:	2.0mA(5.0V)
Color of LED Unit:	Yellow-Green
Current of LED Unit:	<100mA
Color of LCD unit:	Yellow-Green(TN)
Character Size:	2.95X4.35(WXH)mm
Operating Temperature:	0~+50
Storage Temperature:	-20~+70

2. PIN DESCRIPTION:

PIN	SYMBOL	SIGNAL DESCRIPTION
1	VSS	GND
2	VDD	Power Supply
3	V0	Power Supply LCD Driver
4	RS	Register Select-LOW=Instruction,HIGH=Data
5	R/W	Read/Write LOW=MPU to LCM,HIGH=LCM to MPU
6	E	Enable R/W=LOW:Data are talking over at falling edge R/W=HIGH:Data can be read at E=1
7 to 14	DB0 to DB7	Data BUS-Software Selectable 4 or 8bit mode
15	BLK	Cathode of LED Unit
16	BLA	Anode of LED Unit

3. EXTERNAL DIMENSION:



3. REFERENCE WEBPAGE: <http://www.sunman.com.cn/lcm/product/SMC1602A.html>